

Brake Fluid Max

Co-Branded Fluid of Ashok Leyland & Gulf Oil

Product Description

Brake Fluid Max is a heavy-duty brake fluid exclusively developed for hydraulic clutches and brakes of Ashok Leyland vehicles. It provides excellent protection to the hydraulic clutch and braking system components.

Features and Benefits

- Excellent lubricity to ensure lubrication and adequate protection to all clutch and brake system components
- Good viscosity control over wide temperature range facilitates quick and smooth response
- Good chemical stability ensures long trouble free service life
- Excellent seal swell characteristics helps in minimising leakage
- Compatible with other materials in the clutch and brake system

Applications

The only co-branded fluid approved by Ashok Leyland for hydraulic clutches and brakes of Ashok Leyland vehicles for a drain interval of 40,000 Kms.

Specifications, Approvals & Typical Properties

| Specifications | | DOT 3 |
|--------------------------------------|-------------|--|
| US FMVSS DOT 3 | | SAE J 1703 |
| IS 8654 | | ISO 4925 |
| Approvals | | |
| Ashok Leyland | | Approved as co-branded fluid for hydraulic clutches and brakes |
| Typical Properties | | |
| Test Parameters | Test Method | Typical Values |
| Colour | | Red |
| Equilibrium Reflex Boiling Point, °C | IS 8654 A-1 | 215 |
| pH | IS 8654 A-3 | 9.0 |
| Viscosity @ -40 °C, cSt | ASTM D 445 | 1300 |
| Viscosity @ 100 °C, cSt | ASTM D 445 | 2.0 |

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com