

Gear XP Max 90

Co-Branded Oil of Ashok Leyland & Gulf Oil

Product Description

Gear XP Max 90 is a premium quality Extreme Pressure type gear oil exclusively developed for new generation synchromesh/constant mesh gear boxes and steering gears of Ashok Leyland vehicles.

It is formulated using high quality base oils and proven performance additives to provide unmatched protection to gear components. It possesses excellent oxidation stability and wear protection.

Features and Benefits

- High performance extreme pressure additive technology ensures excellent wear control and offers maximum gear and bearing protection
- Shields against rusting and corrosion of components
- Superior oxidation stability protects against oxidation degradation and facilitates long drain intervals

Applications

- The only co-branded engine oil approved by Ashok Leyland as co-branded gear oil for following drain intervals :
 - 40,000 kms in constant mesh and synchromesh gear boxes
 - 72,000 kms in manual steering gears

Specifications, Approvals & Typical Properties

Specifications		90
API GL-4		DaimlerChrysler MB 235.1
US Military MIL-L-2105		MAN 341 Type N
IS : 1118 GL-4		ZF TE ML 17A/B
Approvals		
Ashok Leyland		Approved as co-branded gear oil for constant mesh and synchromesh gear boxes and manual steering gears
Typical Properties		
Test Parameters	ASTM Method	Typical Values
Viscosity @ 100 °C, cSt	D 445	18.0
Viscosity Index	D 2270	95
Flash Point, °C	D 92	210
Pour Point, °C	D 97	-12
Density @ 15°C, Kg/l	D 1298	0.89

Properties mentioned above are typical only and minor variations, which do not affect the product performances, are to be expected in normal manufacturing. The above information is based on past history of the grade only and must not be construed as a guarantee of performance. Follow equipment manufacturer's recommendations for performance level and viscosity grade. The Material Safety Data Sheet for this product is available from your nearest Gulf Distributor.

Gulf Oil International

The information contained herein is believed to be correct at time of publication. No warranty expressed or implied is given concerning the accuracy of the information or the suitability of the products. Gulf Oil International reserves the right to modify and change its products and specifications without prior notice.

www.gulfoilltd.com